

Product : 25mm 30kg/m³ Xpe Grey Plate

SPECIFICATIONS	VALUES	UNIT	RELATED STANDARD
Thickness Density Width Length Color Tensile	25±%10	mm	TS EN 823 TS
strenght (production lengthwise)* Tensile	30±%10	kg/m ³	EN 1602 TS EN
strenght (production across)* Elongation At	73±2	cm-cm	822 TS EN 822
Break (production lengthwise)* Elongation At	113±3 Grey		
Break (production across)* Compression	>200 >200	-	-
Stress Value @ %10 Compression Stress	>70 >70	kPa	EN ISO 1798
Value @ % 25 Compression Stress Value @	>10 >30	kPa	EN ISO 1798
% 50	>80	% %	EN ISO 1798
*Tests are performed at 10mm semiproduct.		kPa	EN ISO 1798
		kPa	EN ISO 3386
		kPa	EN ISO 3386
			EN ISO 3386

STORAGE	Store in a closed area and protect from direct sunlight.
SAFETY & HEALTY INFORMATION	There is no self-ignition and explosion feature. There is no toxic effect, if contact with the skin.

NOTE : This information has been obtained by laboratory studies. TYT Pack System is not responsible from the mistakes of the wrong applications and usages.